

Technical Specification Sheet
Kingdom Plywood

Standard Plywood

Face & Back	Okoume, Bintangor, Meranti, Poplar, Birch, Pine, Paulonia, Red Canarium, Keruing, Gurjan, Other Hardwood etc.
Core	Poplar, Pine, Eucalyptus, Birch Throughout, Paulonia, Combi, Mixed Hardwood, Keruing, Gurjan etc.
Glue	MR, Melamine, WBP, 72Hours BWP
Formaldehyde Emission Class	E1/E2/Custom
Thickness	2mm, 2.5mm, 2.7mm, 3mm, 3.2mm, 3.6mm, 4mm, 4.8mm, 5mm, 5.2mm, 5.5mm, 6mm, 7mm, 8mm, 9mm, 10mm, 11mm, 12mm, 15mm, 16mm, 17mm, 18mm, 20mm, 21mm, 22mm, 25mm, 28mm, 30mm
Size	915x2135mm, 1220x2440mm, 1250x2500mm, 1500x3000mm, 2000x5200mm
Grade	A/B, B/C, BB/CC, DBB/CC, C+/C, C/D, D/D, E/D
Application	Furniture, Construction, Decoration, Packaging

Note: Calibrated Plywood is also available on request

- The results indicated in the table above refer to average values obtained in laboratory tests. However, there could be small variations in the tests reproduced in other laboratories and under other usage conditions.
- "Kingdom Quality Promise" - We will continuously try to improve the specifications mentioned here as part of our DNA of Continuous Improvement and of delivering Value to our customers each and every time.